

Stuffing Boxes

Features

- Available in single or dual pack
- Cap, glands, body and base made of Grade 65-45-12 ductile iron
- API gauged threads
- Bottom threads available in API tubing [EUE] or LP [line pipe]
- Built-in misaligning feature
- Available for the following rod sizes: 1", 1-1/8", 1-1/4", 1-1/2" and 1-3/4"



Cone Packing

Features

- Available for following rod sizes: 1", 1-1/8", 1-1/4", 1-1/2" and 1-3/4"
- Available in a variety of compounds including:
 - Gold Flake
 - Special Lube
 - Soft Cone
 - Teflon Filled
 - High Temperature
- Hydrogen saturated nitrile available for H₂S service



SOFT	For normal pumping wells. Standard packing in all WNS stuffing boxes for any type polished rod or liner.
HARD	For wells that produce large volumes of water. Use only on hard-faced liner.
SPECIAL LUBRICATED	Self-contained lubricant for wells with an absence of fluid.
HEAVY DUTY	For wells that pump or flow off.
HIGH TEMP	For high-temperature applications to 425°F.
TEFLON FILLED	Longer-lasting for pumping situations such as long stroke, fast cycle, lack of lubrication.
BRASS TEFLON	Combines the longevity of Teflon with the cleaning action of brass. Used on steel polished rods, or hard-faced liners only.
TYPE WN-G	For wells with H ₂ S or in CO ₂ service.
BOTTOM CLEANER CONES	Helps prevent undesirable deposits on polished rods, or liners.

